Image				0.	0.				
Model	JLEU3	JLEU4	JLEU5	JLEU5WP	JLEU6	JLEU9	JLEU10	JLEU12	JLEU15
Product Weight	1.54lbs/0.7k gs	1.54lbs/0.7k gs	1.32lbs/0.6k gs	2.31lbs/1.05 kgs	3.45lbs/1.57 kgs	1.65lbs/0.75 kgs	0.66lbs/0.3kgs		0.88lbs/0.4k gs
Product Size	34.2×8.8×1 0.9cm	30.15×5.87 ×13.1cm	28×6.75×11 cm	31.2×10.62 ×13.3cm	32×7.2×12. 5cm	30.75×9.8× 11.4cm	21.6×4.5×10c m	23.7×5.5×1 1.6cm	23.6×4.25×1 1cm
Color	White	White	White	White	White	White	White	White	White
Material	Thermoplast	Thermoplast	Thermoplast	Thermoplast	Thermoplast	Thermoplast	Thermoplastic	_	Thermoplasti
Voltage	120/277 volts	120/277 volts	120/277 volts	120/277 volts	120-277 volts	120/277 volts	120/277 volts	120-277 volts	120-277 volts
Battery	3.6V 1000mAh Ni-Cad	3.6V 1000mAh Ni-Cad	3.6V 1000mAh Ni-Cad	3.6V 2000mAh Ni-Cd	6V 4Ah Lead Acid	3.6V 1000mAh Ni-Cad	3.6V 1000mAh Ni-Cad	3.6V 1000mAh Ni-Cad	3.6V 1000mAh Ni-MH
Wattage	2.4 W	2W	2W	2.4W	3.28-4.14wa	2.4 W	0.88W	4.5 W	1.1W
Type of Bulb	LED	LED	LED	LED	LED	LED	LED	LED	LED
Mounting	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted
Certification			UL&cUL, CEC, DOE, FCC, ROHS						
Weather Rating	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location	Listed for damp location
Carton Weight	11.02lbs/5k gs	11.02lbs/5k gs	8.82lbs/4kgs	16.09lbs /7.3kgs	20.72lbs /9.4kgs	4.62kgs	8.82lbs/4kgs	7.72lbs/3.5k gs	12.13lbs/5.5 kgs
Carton Size (L×W×H)	37×21×38c m/6pcs	32×29.5×26 cm/6pcs	30×24×25c m/6pcs	45.2×34×27 .5cm/6pcs	33.5×27.5× 25cm	40.7×32.5× 23cm/6pcs	35.5×24.5×23 cm/12pcs	26.5×26×21 cm/6pcs	38×25.5×22. 5cm/12pcs
Charging Time	24 hours	24 hours	24 hours	24 hours	24 hours	24 hours	24 hours	24 hours	24 hours
Emergency Run Time	≥90 mins	≥90 mins	≥90 mins	≥90 mins	≥90 mins	≥90 mins	≥90 mins	≥90 mins	≥90 mins