

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Suitable for wall mount applications.
- Universal J-box mounting pattern.
- 120V-277VAC Universal voltage operation.
- 2pcs 1W ultra bright LED lamp heads for emergency mode.
- Luminous Flux: more than 200 LM.
- Built-in 3.6V1000mAh Ni-MH battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

ORDERING INFORMATION

FAMILY	HOUSING COLOR	REMOTE CAPACITY
JLEU15	BLANK(WHITE)	BLANK(WITHOUT)
	B(BLACK)	RC(WITH REMOTE)

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLEU15	37.5x25.5x22cm/12pcs	4.5/3.5kgs
JLEU15RC	37.5x25.5x22cm/12pcs	5.5/4.5kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLEU15	120-277V	0.02A	1.1W	2pcs 1W ultra bright LED lamp heads	24 Hrs	90 Mins
JLEU15RC	120-277V	0.02A	1.5W	2x1W ultra bright LED lamp+2W remote load	24 Hrs	90 Mins

FAMILY: **JLEU15**

NOTES:

TYPE: **COMPACT SIZE DUAL HEAD EMERGENCY LIGHT**



CEC DOE FC

