

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes
- Suitable for wall mount applications
- Universal J-box mounting pattern
- 120V-277VAC Dual voltage operation
- 2X3pcs Super bright LED lamp heads for emergency mode, provide more than 650Lm output.
- Built-in 6V4AH Lead Acid battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time
- Test switch and charge indicator
- UL and cULus listed
- 0° to 40°C indoor damp location listed

ORDERING INFORMATION

FAMILY	HOUSING COLOR	OPTIONS
JLEU6	BLANK(WHITE)	HO(HIGH OUTPUT)
	B(BLACK)	

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLEU6	35x29x26cm/6pcs	9.4/8.2kgs
JLEU6 HO	35x29x26cm/6pcs	9.4/8.2kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLEU6	120-277V	0.054-0.036A	3.28-4.14W	2X3Pcs Super bright LED	24 Hrs	90 Mins
JLEU6 HO	120-277V	0.054-0.036A	3.28-4.5W	6X2W Super bright LEDs	24 Hrs	90 Mins

FAMILY: **JLEU6**

NOTES:

TYPE: **HIGH OUTPUT DUAL HEAD EMERGENCY LIGHT**

CEC DOE FC

