

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6"height with 3/4"stroke.Optional RED or GREEN letters.
- SALIDA faceplate available.
- Single or double face(Universal)
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- Ultra bright RED or GREEN LEDs.
- Built-in 1.2V1000mAh Nickel cadmium battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

ORDERING INFORMATION						
FAMILY	LENS	HOUSING COLOR				
JEE2	R(RED)	BLANK(WHITE)				
	G(GREEN)	B(BLACK)				
	ТҮРЕ	LETTER				
	BLANK(AC ONLY)	BLANK(EXIT)				
	E(BATTERY BACKUP)	SA(SALIDA)				

PACKING INFORMATION							
MODEL NO.	PACKING INFORMATION	WEIGHTS					
JEE2RWE	40x33x23cm/6pcs	6.2/5.7kgs					
JEE2GWE	40x33x23cm/6pcs	6.2/5.7kgs					
JEE2RW AC ONLY	40x33x23cm/6pcs	6.0/5.5kgs					
JEE2GW AC ONLY	40x33x23cm/6pcs	6.0/5.5kgs					

FAMILY:	JEE2
NOTES:	
TYPE:	NEW COMPACT SIZE LED EXIT SIGN














ELECTRICAL INFORMATION								
MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME		
JEE2RW	120/277V	0.015/0.008A	1.9W	12Pcs Red LEDs	24 Hrs	90 Mins		
JEE2GW	120/277V	0.015/0.008A	1.9W	6Pcs Green LEDs	24 Hrs	90 Mins		
JEE2RWE	120/277V	0.020/0.020A	1.8W	12Pcs Red LEDs	24 Hrs	90 Mins		
JEE2GWE	120/277V	0.020/0.020A	1.8W	6Pcs Green LEDs	24 Hrs	90 Mins		
JEE2GW-SA	120/277V	0.015/0.008A	1.9W	6Pcs Green LEDs	24 Hrs	90 Mins		