

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke. Optional RED or GREEN letters.
- SALIDA faceplate available.
- Single or double face(Universal)
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- 2X1W SMT LED lamp heads for emergency mode.
- Built-in 3.6V1000mAh Nickel cadmium battery for minimum 90 minutes emergency operation.
- Built-in 3.6V2000mAh Nickel cadmium battery for minimum 90 minutes emergency operation. (JLECB2RWRC)
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

ORDERING INFORMATION

FAMILY	LENS	HOUSING COLOR	REMOTE CAPACITY	LETTER
JLECB2	R(RED)	W(WHITE)	BLANK(WITHOUT)	BLANK(EXIT)
	G(GREEN)	B(BLACK)	RC(WITH REMOTE)	SA(SALIDA)

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLECB2RW	40x33x23cm/6pcs	7.0/6.5kgs
JLECB2GW	40x33x23cm/6pcs	7.0/6.5kgs
JLECB2RWRC	40x33x23cm/6pcs	7.2/6.2kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLECB2RW	120/277V	0.03-0.013A	3.5W	6pcs ultra bright RED LED +2x1W LED Lamp Assembly	24 Hrs	90 Mins
JLECB2GW	120/277V	0.03-0.013A	3.5W	6pcs ultra bright GREEN LED +2x1W LED Lamp Assembly	24 Hrs	90 Mins
JLECB2RWRC	120/277V	0.03-0.013A	3.5W	6pcs ultra bright RED LED +2x1W LED Lamp Assembly +2W Remote Lamps	24 Hrs	90 Mins

FAMILY: JLECB2

NOTES:

TYPE: NEW SLIM EXIT/EMERGENCY COMBO



CEC DOE FC

